



Key Features

- Larger cooling capacity
- Dual evaporators
- No ducting required
- Standard and 24V thermostat options available
- Allows for maximum racking space
- Is virtually invisible in the cellar
- Easy installation and accessibility
- Includes a condensate pump system
- Grilles of evaporator units come with a paintable primer finish

Features

Our latest Ceiling Mount split system is a dual-evaporator design. Cellar contractors have asked for a powerful yet aesthetic design which does not reduce racking capacity. Our Ceiling Mount Twin system incorporates these advantages and more. In addition to offering excellent efficiency (by drawing in the warm air which accumulates at the ceiling and cooling and dispersing it throughout the cellar), the Ceiling Mount Twin allows for maximum racking space and can be fully recessed into the ceiling of the cellar. Designed with the highest-quality professional-grade parts for longevity and performance, the Ceiling Mount Twin system also offers ease of installation and accessibility. It includes a condensate pump system to get rid of excess moisture, and the grilles of the evaporators feature a basic primer finish which can be painted to match the cellar decor. Our new Ceiling Mount Twin split system combines flexibility of color and design, dual evaporators for proven cooling performance, and the quality and reliability which contractors have come to expect from WhisperKOOL.

Specifications

Cellar Size	Approx. 3000 cu. ft.	
BTUh w/90° air entering the condenser coil	8500	
CFM	308	
Dimensions	Evaporator: 12.75"H x 14.5"W x 35.75"D (x2) W/mounting bracket: 17.10"H x 38.75"D (x2)	Condensing Unit: 24"L x 17.5"W x 13.4"H
Refrigerant	R-404a	
Condensing Unit HP	3/4	
Voltage Rating	Evaporator: 115V (20 amp Dedicated Curcuit Required)	Condensing Unit: 230V (20 amp Dedicated Curcuit Required)
Weight	Evaporator: 80lbs	Condensing Unit: 67lbs
AMPS (starting/running)	Evaporator: 2/1	Condensing Unit: 27/7.3
dBA	58.5	
Drainline	1/4" ID clear plastic tubing (not provided)	
Installation	Evaporator units are installed through the cellar ceiling. Condensing unit is installed outside in a protective enclosure.	
Thermostat	Remote digital display	
Temp. Delta	55°F max temperature differential between cellar temperature and condensing unit air intake temperature	
Warranty	2 year (parts and labor)	

Optional Accessories

24V Thermostat Conversion Kit

