240V SLIMLINE LS PRODUCT SHEET

SLIMLINE LS

240V Self-Contained Unit

FEATURES

- Two speed fan switch
- Up to 45% more capacity
- Customizable front panel
- Through-the-wall installation
- Can be mounted above a door
- Liquid temperature measuring bottle probe
- Strategic relocation of internal components

UNIT SPECS

*Approximated in an environment that is fully insulated and sealed with a proper vapor barrier. Each wine cellar is unique and has specific cooling requirements. Heat load calculations should always be performed prior to selecting a cooling unit.

Model	**Slimline LS**	
Cellar Size	8.5 cu. m*	18.4 cu. m*
Fan Speed	Low	Medium
Watts (15.5°C condenser air intake temperature) Sensible / Total	529/702	651/818
Watts (23.8°C condenser air intake temperature) Sensible / Total	510/689	623/783
Watts (29.4°F condenser air intake temperature) Sensible / Total	504/646	582/704
Dimensions	54.6cm L x 56.3cm W x 26.2cm H	
Refrigerant	R-134a	
Voltage Rating	240V (15-amp dedicated circuit required)	
Weight (kg)	37 kg without packaging, 41 kg with packaging	
Amps	3 (Running Amps)	
Drain Line	12.7mm ID clear plastic tubing	
Installation	Through the wall, ideally above a doorway	
Thermostat	Advanced digital display, liquid-temperature-measuring bottle probe (retractable cable)	
Temp. Delta	Can maintain a 13°C cellar temperature with up to 29°C condenser air intake temperature.	
Warranty	Two-year limited warranty (parts and labor)	